

View Online at <https://aerobasegroup.com/nsn/4320-01-033-1243>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Alkali solution and hydrochloric acid and nitric acid and sulfuric acid

Pump Quantity:

1

Cooling Method:

Self ventilated

End Application:

Used with portable fluid analyzer onboard 210 ft wmec and various other coast guard vessels

Maximum Discharge Flow Rate:

55.0 gallons per minute

Total Head:

75.000 feet

Suction Lift:

20.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400