

View Online at <https://aerobasegroup.com/nsn/4320-01-036-4861>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1 and 1

Intake Connection Quantity:

2

Intake Connection Type:

Unthreaded external and unthreaded external

Discharge Connection Quantity:

2

Discharge Connection Type:

Unthreaded external and unthreaded external

Current Type:

Ac

Pump Quantity:

2

Maximum Discharge Flow Rate:

4.8 gallons per minute and 4.8 gallons per minute

Total Head:

3.000 feet and 3.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute and 3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

2

Centrifugal Pump Impeller Suction Type:

Single and single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

10.600 inches

Unpackaged Unit Width:

4.5000 inches

Unpackaged Unit Height:

6.300 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

0.8

Features Provided:

Self-priming

Prime Mover Power Rating:

0.125 horsepower

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Same as 4320-00-478-7108 except less weld screws 181391 on motor housing

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400