

View Online at <https://aerobasegroup.com/nsn/4320-01-036-4861>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1 and 1

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Unthreaded external and unthreaded external

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Unthreaded external and unthreaded external

**Current Type:**

Ac

**Pump Quantity:**

2

**Maximum Discharge Flow Rate:**

4.8 gallons per minute and 4.8 gallons per minute

**Total Head:**

3.000 feet and 3.000 feet

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute and 3450.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single and single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

10.600 inches

**Unpackaged Unit Width:**

4.5000 inches

**Unpackaged Unit Height:**

6.300 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

0.8

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.125 horsepower

**Voltage In Volts:**

230.0

**Phase:**

Single

**Special Features:**

Same as 4320-00-478-7108 except less weld screws 181391 on motor housing

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400