

View Online at <https://aerobasegroup.com/nsn/4320-01-036-6213>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Rectangular flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Rectangular flange

Current Type:

Ac

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

75.0 gallons per minute

Discharge Pressure:

175.0 pounds per square inch gage

Total Head:

185.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

23.0

Features Provided:

Self-priming

Prime Mover Power Rating:

7.5 horsepower

Voltage In Volts:

208.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400