

View Online at <https://aerobasegroup.com/nsn/4320-01-038-0460>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Dust-ignition proof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

3.3 gallons per minute

**Discharge Pressure:**

30.0 pounds per square inch gage

**Total Head:**

50.000 feet

**Suction Lift:**

20.000 feet

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

8.5

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 unj

**Intake Connection Thread Size And Series/type Designator:**

1.062-12 unj

**Features Provided:**

Self-priming

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400