

View Online at <https://aerobasegroup.com/nsn/4320-01-040-9522>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Ethylene glycol

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Ethylene glycol

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

8.5 gallons per minute

Discharge Pressure:

7.5 pounds per square inch gage

Total Head:

19.000 feet

Operating Speed At Rated Capacity:

3200.0 revolutions per minute

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

7.281 inches

Unpackaged Unit Width:

4.6850 inches

Unpackaged Unit Height:

4.781 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.35

Discharge Connection Thread Size And Series/type Designator:

0.500-14 npt

Intake Connection Thread Size And Series/type Designator:

0.750-14 npt

Prime Mover Power Rating:

0.050 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400