

View Online at <https://aerobasegroup.com/nsn/4320-01-048-6559>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Trailer

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Dc

**Media For Which Designed:**

Foam

**Environmental Protection:**

Explosion proof

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

53.8 gallons per minute

**Discharge Pressure:**

13.5 pounds per square inch gage

**Total Head:**

31.200 feet

**Suction Lift:**

1.300 feet

**Operating Speed At Rated Capacity:**

457.1 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Knuckle

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

21.5

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

1.500-11 1/2 npt

**Prime Mover Power Rating:**

0.750 horsepower

**Voltage In Volts:**

28.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400