

View Online at <https://aerobasegroup.com/nsn/4320-01-048-6559>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Trailer

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Foam

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

53.8 gallons per minute

Discharge Pressure:

13.5 pounds per square inch gage

Total Head:

31.200 feet

Suction Lift:

1.300 feet

Operating Speed At Rated Capacity:

457.1 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Knuckle

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

21.5

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11 1/2 npt

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400