

View Online at <https://aerobasegroup.com/nsn/4320-01-055-4059>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Oval flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Oval flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

100.0 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Total Head:

5.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

0.250 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400