

View Online at <https://aerobasegroup.com/nsn/4320-01-056-0644>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Ferrous sulfate

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

88.0 gallons per minute

**Discharge Pressure:**

48.0 pounds per square inch gage

**Total Head:**

105.000 feet

**Operating Speed At Rated Capacity:**

3400.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Discharge Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

3.000 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Solution tank mounted

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400