NSN 4320-01-058-8536

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-058-8536

Prime Mover Quantity:		
1		
Prime Mover Cooling Medium:		
Oil		
Mounting Type:		
Base		
Intake Connection Quantity:		
1		
Intake Connection Type:		
Threaded internal		
Discharge Connection Quantity:		
1		
Discharge Connection Type:		
Threaded internal		
Media For Which Designed:		
Hydrocarbon fuels and oils		
Environmental Protection:		
Explosion proof		
Pump Quantity:		
1		
Cooling Method:		
Self ventilated		
Maximum Discharge Flow Rate:		
20.0 gallons per minute		
Discharge Pressure:		
50.0 pounds per square inch gage		
Pumping Element Operating Position:		
Horizontal		
Rotary Pump Design:		
Gear		
Prime Mover Type:		
Electric motor		
Inclosure Type:		
Partially enclosed		
Discharge Connection Thread Size And Series/type Designator:		
1.000-18 npt		
Intake Connection Thread Size And Series/type Designator:		
1.500-18 npt		
Prime Mover Power Rating:		
1.000 horsepower		
Voltage In Volts:		
208.0		

NSN 4320-01-058-8536

Rotary Pump Unit - Page 2 of 2



\mathbf{r}	naea.	
	Hase.	

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400