

View Online at <https://aerobasegroup.com/nsn/4320-01-061-6535>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

2

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Liquid

Pump Quantity:

2

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

6.7 gallons per minute and 6.7 gallons per minute

Total Head:

16.100 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

2

Centrifugal Pump Impeller Suction Type:

Single

Volume Control Type:

Rotary

Control Location:

Center

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

0.8

Prime Mover Power Rating:

0.125 horsepower

Voltage In Volts:

230.0

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400