NSN 4320-01-071-2474

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-071-2474

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Round flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Round flange |
| Current Type: |
| Ac |
| Environmental Protection: |
| Dripproof |
| Pump Quantity: |
| 1 |
| Maximum Discharge Flow Rate: |
| 30.0 gallons per minute |
| Total Head: |
| 346.000 feet |
| Operating Speed At Rated Capacity: |
| 3500.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Pump Basic Material: |
| Iron |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Open |
| Prime Mover Power Rating: |
| 10.000 horsepower |

NSN 4320-01-071-2474

Centrifugal Pump Unit - Page 2 of 2



| Voltage | In ' | Vol | ts: |
|----------|------|-----|-----|
| 230.0 an | d 4 | 60 | .0 |

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A19400