

View Online at <https://aerobasegroup.com/nsn/4320-01-073-0082>

**Prime Mover Quantity:**

1

**Mounting Type:**

Base

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Compression tube

**Media For Which Designed:**

Hydrocarbon fuels and oils and water, fresh

**Pump Quantity:**

1

**End Application:**

2350-01-061-2445

**Maximum Discharge Flow Rate:**

2.7 gallons per minute

**Discharge Pressure:**

270.0 pounds per square inch gage

**Total Head:**

15.000 feet

**Suction Lift:**

4.130 feet and 4.370 feet

**Operating Speed At Rated Capacity:**

2376.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Hydraulic motor

**Special Features:**

Material used-aluminum; prime per tt-p-636 or tt-p-1757; white topcoat per tt-e-489

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400