## NSN 4320-01-076-6502

Rotary Pump Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-076-6502

| Prime Mover Quantity:               |
|-------------------------------------|
| 1                                   |
| Mounting Type:                      |
| Base                                |
| Intake Connection Quantity:         |
| 1                                   |
| Intake Connection Type:             |
| Round flange                        |
| Discharge Connection Quantity:      |
| 1                                   |
| Discharge Connection Type:          |
| Round flange                        |
| Media For Which Designed:           |
| Hydrocarbon fuels and oils          |
| Pump Quantity:                      |
| 1                                   |
| Maximum Discharge Flow Rate:        |
| 25.0 gallons per minute             |
| Discharge Pressure:                 |
| 25.0 pounds per square inch gage    |
| Suction Lift:                       |
| 11.300 feet                         |
| Operating Speed At Rated Capacity:  |
| 1050.0 revolutions per minute       |
| Pumping Element Operating Position: |
| Horizontal                          |
| Rotary Pump Design:                 |
| Vane                                |
| Operation Relationship Design:      |
| Simultaneous                        |
| Prime Mover Type:                   |
| Pneumatic motor                     |
| Prime Mover Power Rating:           |
| 1.200 horsepower                    |
| Shelf Life:                         |
| N/a                                 |
| Unit Of Measure:                    |
|                                     |
| Demilitarization:                   |
| No                                  |
| Fiig:                               |
| A19400                              |
|                                     |