NSN 4320-01-077-3998

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-077-3998

Manualina Tomas
Mounting Type:
Frame
Intake Connection Quantity:
1
Intake Connection Type:
Rectangular flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Rectangular flange
Drive Connection Type:
Flexible coupled
Media For Which Designed:
Hydrocarbon fuels and oils
End Application:
Used in c.P.P. Servo system onboard 378 ft whec coast guard vessels
Maximum Discharge Flow Rate:
33.8 gallons per minute
Discharge Pressure:
1000.0 pounds per square inch gage
Total Head:
6.000 feet
Suction Lift:
10.000 feet
Operating Speed At Rated Capacity:
1200.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Counterclockwise
Volume Control Type:
Pressure compensation
Rotary Pump Design:
Vane
Operation Method:
Operation Method: Powered
Powered
Powered Drive Shaft Type:
Powered Drive Shaft Type: Key type, external

2.750 inches

NSN 4320-01-077-3998

Rotary Pump - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400