NSN 4320-01-078-5230



Centrifugal Pump - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4320-01-078-5230 **Mounting Type:** Base Stage Quantity: **Intake Connection Quantity: Intake Connection Type:** Threaded external **Discharge Connection Quantity: Discharge Connection Type:** Threaded internal and unthreaded external **Drive Connection Type:** Close coupled Media For Which Designed: Sewage and water, fresh **Maximum Discharge Flow Rate:** 12.5 gallons per minute **Discharge Pressure:** 25.0 pounds per square inch gage **Total Head:** 75.000 feet **Operating Speed At Rated Capacity:** 1725.0 revolutions per minute **Pumping Element Operating Position:** Horizontal **Pump Rotation Direction:** Clockwise Centrifugal Pump Design: Mixed flow **Centrifugal Pump Impeller Quantity: Centrifugal Pump Impeller Suction Type:** Single **Drive Shaft Type:** Machine keyway

Drive Shaft End Diameter: 0.625 inches **Drive Shaft Length:** 1.438 inches **Pump Basic Material: Bronze**

NSN 4320-01-078-5230

Centrifugal Pump - Page 2 of 2

Fiig: A19400



| Discharge Connection Thread Size And Series/type Designator: |
|--|
| 1.000-11-1/2 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 1.500-11-1/2 npt |
| Special Features: |
| Neoprene impeller |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |