

View Online at <https://aerobasegroup.com/nsn/4320-01-093-4473>

**Prime Mover Quantity:**

1

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Bell mouth

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Quick disconnect

**Current Type:**

Ac

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

150.0 gallons per minute

**Total Head:**

135.000 feet

**Operating Speed At Rated Capacity:**

3400.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

2

**Unpackaged Unit Height:**

41.000 inches

**Pump Basic Material:**

Aluminum

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

28.0 and 14.0 and 11.2

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

11.000 horsepower

**Voltage In Volts:**

230.0 and 460.0 and 575.0

**Phase:**

Three

**Special Features:**

Submersible to 65 ft; integral strainer included; 3 in. Discharge

**Frequency In Hertz:**

60.0

**Reference Number Differentiating Characteristics:**

As differentiated by impeller and voltage

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400