

View Online at <https://aerobasegroup.com/nsn/4320-01-099-9649>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Explosion proof

Pump Quantity:

1

Maximum Discharge Flow Rate:

8.0 gallons per minute

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Prime Mover Power Rating:

0.500 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Viking pump gg195d cast iron fitted, mecanical seal, no relief valve

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400