

View Online at <https://aerobasegroup.com/nsn/4320-01-100-2725>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Pump Quantity:

1

Discharge Pressure:

55.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Gasoline engine

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

2.500 horsepower

Special Features:

Splash shielded engine, muffler and fuel fill cap; spark arresting muffler; shielded ignition; flame safe for transfer of flammable petroleum products

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400