

View Online at <https://aerobasegroup.com/nsn/4320-01-115-3474>

Prime Mover Quantity:

1

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Maximum Discharge Flow Rate:

10.4 gallons per minute

Discharge Pressure:

8.6 pounds per square inch gage

Total Head:

20.0 meters

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400