

View Online at <https://aerobasegroup.com/nsn/4320-01-118-2005>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Sewage

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Cubic Measure:**

6.0000 cubic feet

**End Application:**

Sewage system onboard 140 ft wtgb c.G. Vessels

**Maximum Discharge Flow Rate:**

30.0 gallons per minute

**Total Head:**

70.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

11.0

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

5.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400