

View Online at <https://aerobasegroup.com/nsn/4320-01-118-2006>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Cubic Measure:

3.7159 cubic feet

End Application:

Item irty oil pump on board 270 ft wmec cg vessels

Maximum Discharge Flow Rate:

10.0 gallons per minute

Discharge Pressure:

60.0 pounds per square inch gage

Operating Speed At Rated Capacity:

870.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Volume Control Type:

Rotary

Control Location:

Left side

Rotary Pump Design:

Gear

Unpackaged Unit Length:

36.5000 inches

Unpackaged Unit Width:

12.0000 inches

Unpackaged Unit Height:

14.600 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

3.2

Prime Mover Power Rating:

1.5 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Pump and motor are mounted to a steel base

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400