NSN 4320-01-118-2006

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-118-2006

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Frame
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Hydrocarbon fuels and oils
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Self ventilated
Cubic Measure:
3.7159 cubic feet
End Application:
Item irty oil pump on board 270 ft wmec cg vessels
Maximum Discharge Flow Rate:
10.0 gallons per minute
Discharge Pressure:
60.0 pounds per square inch gage
Operating Speed At Rated Capacity:
870.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Volume Control Type:
Rotary
Control Location:
Left side
Rotary Pump Design:

Gear

NSN 4320-01-118-2006

Rotary Pump Unit - Page 2 of 2



Unpackaged Unit Length:
36.5000 inches
Unpackaged Unit Width:
12.0000 inches
Unpackaged Unit Height:
14.600 inches
Prime Mover Type:
Electric motor
Inclosure Type:
Open
Current Rating In Amps:
3.2
Prime Mover Power Rating:
1.5 horsepower
Voltage In Volts:
440.0
Phase:
Three
Special Features:
Pump and motor are mounted to a steel base
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400