Reciprocating Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-119-8113

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Liquid
Mounting Type:
Base
Cylinder Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Media For Which Designed:
Liquid
Environmental Protection:
Waterproof
Pump Quantity:
1
Pumping Element Type:
Diaphragm
Cooling Method:
Air to air cooled
End Application:
Distilling plant onboard 270 ft wmec class coast guard vessels
Discharge Pressure:
925.0 pounds per square inch gage
Operating Speed At Rated Capacity:
117.0 strokes per minute
Pumping Element Operating Position:
Horizontal
Pump Reciprocating Design:
Single acting
Reciprocating Stroke Type:
Variable
Prime Mover Type:
Electric motor

## NSN 4320-01-119-8113

Reciprocating Pump Unit - Page 2 of 2



Inclosure Type:
Fully enclosed
Current Rating In Amps:
1.6
Discharge Connection Thread Size And Series/type Designator:
0.250-18 npt
Intake Connection Thread Size And Series/type Designator:
0.250-18 npt
Prime Mover Power Rating:
0.250 horsepower
Voltage In Volts:
208.0 and 230.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400