NSN 4320-01-119-8113



Reciprocating Pump Unit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4320-01-119-8113 **Prime Mover Quantity: Prime Mover Cooling Medium:** Liquid **Mounting Type:** Base **Cylinder Quantity: Intake Connection Quantity: Intake Connection Type:** Threaded internal **Discharge Connection Quantity: Discharge Connection Type:** Threaded internal **Current Type:** Ac Media For Which Designed: Liquid **Environmental Protection:** Waterproof **Pump Quantity: Pumping Element Type:** Diaphragm **Cooling Method:** Air to air cooled **End Application:** Distilling plant onboard 270 ft wmec class coast guard vessels **Discharge Pressure:** 925.0 pounds per square inch gage **Operating Speed At Rated Capacity:**

117.0 strokes per minute **Pumping Element Operating Position:** Horizontal **Pump Reciprocating Design:** Single acting **Reciprocating Stroke Type:** Variable **Prime Mover Type:** Electric motor

NSN 4320-01-119-8113

Reciprocating Pump Unit - Page 2 of 2



Inclosure Type:	
Fully enclosed	
Current Rating In Amps:	
1.6	
Discharge Connection Thread Size And Series/type Designator:	
0.250-18 npt	
Intake Connection Thread Size And Series/type Designator:	
0.250-18 npt	
Prime Mover Power Rating:	
0.250 horsepower	
Voltage In Volts:	
208.0 and 230.0	
Phase:	
Three	
Frequency In Hertz:	
60.0	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A19400	