

View Online at <https://aerobasegroup.com/nsn/4320-01-121-0031>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Rectangular flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Main reduction gear, 270 ft wmec coast guard vessels

Maximum Discharge Flow Rate:

29.0 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Total Head:

136.000 feet

Suction Lift:

28.000 feet

Operating Speed At Rated Capacity:

1140.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

11.0

Prime Mover Power Rating:

7.5 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400