NSN 4320-01-125-5271

Hydraulic Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-125-5271

| Torque Load Rating: |
|--|
| 404.1 inch-pounds |
| Mounting Type: |
| Flange |
| Mounting Hole Diameter: |
| 0.562 inches |
| Mounting Hole Quantity: |
| 2 |
| Thread Size: |
| 1.000 |
| Shaft Diameter: |
| 0.875 inches |
| Operating Speed At Rated Capacity In Rpm: |
| 30.0 or 3000.0 |
| Mounting Bolt Circle Diameter: |
| 5.750 inches |
| Screw Thread Series Designator: |
| Bspp |
| Shaft Rotation Direction: |
| Clockwise and counterclockwise |
| Thread Location: |
| Internal |
| Connection Quantity: |
| 2 and 1 and 1 |
| Maximum Working Pressure Rating At Specificationified Tempurature Range: |
| 3000 psi at minus 40 degrees f to plus 180 degrees f |
| Connection Design: |
| Threaded |
| Displacement Type: |
| Constant or variable |
| Constant Displacement Per Revolution: |
| 2.540 cubic inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T103-f |