

View Online at <https://aerobasegroup.com/nsn/4320-01-129-5597>

Prime Mover Quantity:

1

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Oil and water, fresh

Pump Quantity:

1

Discharge Pressure:

75.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Unpackaged Unit Length:

14.0625 inches

Unpackaged Unit Width:

5.6875 inches

Unpackaged Unit Height:

5.750 inches

Pump Basic Material:

Bronze

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.1

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Gear matl bronze; shaft matl stainless steel; pump furnished w/ close-couled motor, stainless steel relief valves and oilless carbon bearings

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400