## NSN 4320-01-132-5513

Centrifugal Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-132-5513

| Stage Quantity:  |
|--|
| 1  |
| Discharge Connection Quantity:                               |
| 1  |
| Discharge Connection Type:                                   |
| Threaded internal  |
| Media For Which Designed:                                    |
| Sewage   |
| End Application:   |
| Sanitation system onboard 210 ft wmec coast guard vessels    |
| Maximum Discharge Flow Rate:                                 |
| 225.0 gallons per minute                                     |
| Discharge Pressure:  |
| 15.0 pounds per square inch gage                             |
| Total Head:  |
| 15.000 feet  |
| Operating Speed At Rated Capacity:                           |
| 1800.0 revolutions per minute                                |
| Pumping Element Operating Position:                          |
| Vertical   |
| Centrifugal Pump Design:                                     |
| Axial flow   |
| Centrifugal Pump Impeller Quantity:                          |
| 1  |
| Centrifugal Pump Impeller Suction Type:                      |
| Single   |
| Discharge Connection Thread Size And Series/type Designator: |
| 4.000-8 npt  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A19400   |
|  |