

View Online at <https://aerobasegroup.com/nsn/4320-01-133-7374>

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Pump Quantity:

1

Maximum Discharge Flow Rate:

10.0 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Suction Lift:

25.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Volume Control Type:

Rotary

Control Location:

Center

Rotary Pump Design:

Flexible member

Prime Mover Type:

Electric motor

Criticality Code Justification:

Feat

Special Features:

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400