NSN 4320-01-133-8772

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-133-8772

Prime Mover Quantity:
1
Stage Quantity:
1
Discharge Connection Quantity:
1
Current Type:
Ac
Environmental Protection:
Dripproof
Pump Quantity:
1
Maximum Discharge Flow Rate:
20.5 gallons per minute
Discharge Pressure:
8.6 pounds per square inch gage
Total Head:
20.000 feet
Operating Speed At Rated Capacity:
3450.0 revolutions per minute
Centrifugal Pump Design:
Axial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Features Provided:
Self-priming
Prime Mover Power Rating:
2.000 horsepower
Voltage In Volts:
230.0 and 460.0
Phase:
Three
Frequency In Hertz:
50.0 and 60.0
Shelf Life:
N/a

NSN 4320-01-133-8772

Centrifugal Pump Unit - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A19400