

View Online at <https://aerobasegroup.com/nsn/4320-01-139-9860>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Hydrocarbon fuels and oils

**Mounting Type:**

Base

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh and sewage

**Environmental Protection:**

Watertight

**Pump Quantity:**

1

**Accessory Components:**

Electric power cable and prime mover controller

**Maximum Discharge Flow Rate:**

104.0 gallons per minute

**Total Head:**

5.000 feet

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Width:**

11.7500 inches

**Unpackaged Unit Height:**

13.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

10.4

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Prime Mover Power Rating:**

0.500 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

130.0 degrees f maximum temp; automatic reset thermal overload protection; 9.750 in.On pt, 3.000 in. Off pt

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400