

View Online at <https://aerobasegroup.com/nsn/4320-01-139-9860>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Hydrocarbon fuels and oils

Mounting Type:

Base

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh and sewage

Environmental Protection:

Watertight

Pump Quantity:

1

Accessory Components:

Electric power cable and prime mover controller

Maximum Discharge Flow Rate:

104.0 gallons per minute

Total Head:

5.000 feet

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Width:

11.7500 inches

Unpackaged Unit Height:

13.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

10.4

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

0.500 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

130.0 degrees f maximum temp; automatic reset thermal overload protection; 9.750 in.On pt, 3.000 in. Off pt

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400