

View Online at <https://aerobasegroup.com/nsn/4320-01-140-9208>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

165.0 gallons per minute and 15.0 gallons per minute

Total Head:

30.000 feet and 80.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Unpackaged Unit Length:

20.625 inches

Unpackaged Unit Width:

12.0000 inches

Unpackaged Unit Height:

9.250 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

9.7 and 4.9

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Prime Mover Power Rating:

3.0 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400