## NSN 4320-01-146-3116

Centrifugal Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-146-3116

| Stage Quantity:  |
|--|
| 1  |
| Intake Connection Quantity:                                  |
| 1  |
| Intake Connection Type:                                      |
| Threaded internal  |
| Discharge Connection Quantity:                               |
| 1  |
| Discharge Connection Type:                                   |
| Threaded internal  |
| Drive Connection Type:                                       |
| Flexible coupled   |
| Maximum Discharge Flow Rate:                                 |
| 200.0 gallons per minute                                     |
| Discharge Pressure:  |
| 85.0 pounds per square inch gage                             |
| Suction Lift:  |
| 15.000 feet  |
| Operating Speed At Rated Capacity:                           |
| 3500.0 revolutions per minute                                |
| Pumping Element Operating Position:                          |
| Horizontal   |
| Pump Rotation Direction:                                     |
| Clockwise  |
| Centrifugal Pump Design:                                     |
| Axial flow   |
| Centrifugal Pump Impeller Quantity:                          |
| 6  |
| Centrifugal Pump Impeller Suction Type:                      |
| Single   |
| Drive Shaft Type:  |
| Woodruff keyway  |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.500-11-1/2 npt   |
| Intake Connection Thread Size And Series/type Designator:    |
| 2.000-11-1/2 npt   |
| Special Features:  |
| W/packing box  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 4320-01-146-3116

Centrifugal Pump - Page 2 of 2



Demilitarization:

No

Fiig:

A19400