

View Online at <https://aerobasegroup.com/nsn/4320-01-156-9985>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air and oil and water, fresh

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Bell mouth

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Cooling Method:**

Water-air cooled

**Maximum Discharge Flow Rate:**

2.8 gallons per minute

**Discharge Pressure:**

2.6 pounds per square inch gage

**Total Head:**

5.000 feet

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

4.125 inches

**Unpackaged Unit Width:**

4.1250 inches

**Unpackaged Unit Height:**

4.250 inches

**Pump Basic Material:**

Plastic

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.1

**Discharge Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.005 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

10.0 ft cord w/3-prong molded plug; ul and csa certified

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400