NSN 4320-01-158-0122

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-158-0122

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Brine
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
360.0 gallons per minute
Discharge Pressure:
35.0 pounds per square inch gage
Total Head:
81.000 feet
Operating Speed At Rated Capacity:
1750.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Operation Relationship Design:
Cincultanaaua

Simultaneous

NSN 4320-01-158-0122

Centrifugal Pump Unit - Page 2 of 2



Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Prime Mover Power Rating:
20.000 horsepower
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A19400