NSN 4320-01-158-3331

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-158-3331

| Intake Connection Quantity: |
|--|
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| End Application: |
| Truck, forklift, model sr40, allis chalmers |
| Maximum Discharge Flow Rate: |
| 10.27 gallons per minute |
| Discharge Pressure: |
| 3000.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 2400.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Counterclockwise |
| Rotary Pump Design: |
| Gear |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| Splined, involute external |
| Drive Shaft Length: |
| 1.085 inches |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.062-12 unf |
| Intake Connection Thread Size And Series/type Designator: |
| 1.312-12 unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A19400 |