

View Online at <https://aerobasegroup.com/nsn/4320-01-163-0693>

Mounting Type:

Flange

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

3

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Close coupled

Media For Which Designed:

Hydrocarbon fuels and oils

End Application:

Fmc corporation cable crane model hc138

Maximum Discharge Flow Rate:

13.5 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Counterclockwise

Rotary Pump Design:

Vane

Operation Method:

Powered

Drive Shaft Type:

Machine keyway

Drive Shaft End Diameter:

0.750 inches

Drive Shaft Length:

2.504 inches

Unpackaged Unit Length:

9.130 inches

Unpackaged Unit Width:

5.130 inches

Unpackaged Unit Height:

4.880 inches

Pump Basic Material:

Steel

Discharge Connection Thread Size And Series/type Designator:

0.750-16 unf and 0.875-14 unf and 0.750-16 unf

Intake Connection Thread Size And Series/type Designator:

1.625-12 un

Special Features:

Outlet port opposite side from inlet; 8gpm, 1750psi relief valve setting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400