NSN 4320-01-170-0909

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-170-0909

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Pump Quantity:
1
Cooling Method:
Blower cooled
End Application:
Navy weapons code jp, supply class aoe
Maximum Discharge Flow Rate:
65.0 gallons per minute
Discharge Pressure:
70.0 pounds per square inch gage
Total Head:
157.000 feet
Operating Speed At Rated Capacity:
3575.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

NSN 4320-01-170-0909

Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:
7.34
Prime Mover Power Rating:
7.5 horsepower
Voltage In Volts:
440.0
Phase:
Three
Special Features:
Navy standard close-coupled horizontal pump spcc i.D. 14n-3500-7.5a4 per mil-p-17840b
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A19400