## NSN 4320-01-171-7158

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-171-7158

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, fresh
Pump Quantity:
1
1 Cooling Method:
Cooling Method:
Cooling Method: Air to air cooled
Cooling Method: Air to air cooled Maximum Discharge Flow Rate:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure: 150.0 pounds per square inch gage
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure: 150.0 pounds per square inch gage  Operating Speed At Rated Capacity:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute  Pumping Element Operating Position:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute  Pumping Element Operating Position: Horizontal
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute  Pumping Element Operating Position: Horizontal  Centrifugal Pump Design: Mixed flow
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute  Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute  Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type:
Cooling Method: Air to air cooled  Maximum Discharge Flow Rate: 660.0 gallons per minute Discharge Pressure: 150.0 pounds per square inch gage Operating Speed At Rated Capacity: 3600.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Mixed flow Centrifugal Pump Impeller Quantity: 1 Centrifugal Pump Impeller Suction Type: Single

Fully enclosed

## **NSN 4320-01-171-7158**Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:
67.7
Prime Mover Power Rating:
40.000 horsepower
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400