NSN 4320-01-172-7767

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-172-7767

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Hydrocarbon fuels and oils
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
38.0 gallons per minute
Discharge Pressure:
19.0 pounds per square inch gage
Total Head:
1386.000 feet
Operating Speed At Rated Capacity:
3555.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

NSN 4320-01-172-7767

Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:

10.3

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

5.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A19400