NSN 4320-01-172-9999

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-172-9999

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Media For Which Designed:
Brine or hydrocarbon fuels and oils or water, fresh
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
2.1 gallons per minute
Discharge Pressure:
20.0 pounds per square inch gage
Operating Speed At Rated Capacity:
1725.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Gear
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Current Rating In Amps:
2.2
Discharge Connection Thread Size And Series/type Designator:
0.250-18 npt
Intake Connection Thread Size And Series/type Designator:

0.250-18 npt

NSN 4320-01-172-9999

Rotary Pump Unit - Page 2 of 2



Prime Mover Power Rating:
0.333 horsepower
Voltage In Volts:
115.0
Phase:
Single
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400