NSN 4320-01-172-9999

Rotary Pump Unit - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4320-01-172-9999

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Brine or hydrocarbon fuels and oils or water, fresh

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

2.1 gallons per minute

Discharge Pressure:

20.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

2.2

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.250-18 npt



NSN 4320-01-172-9999

Rotary Pump Unit - Page 2 of 2



Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A19400