

View Online at <https://aerobasegroup.com/nsn/4320-01-174-4774>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Hydrocarbon fuels and oils

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Liquid

Environmental Protection:

Explosion proof

Pump Quantity:

1

Maximum Discharge Flow Rate:

45.0 gallons per minute and 35.0 gallons per minute and 22.0 gallons per minute and 5.33 gallons per minute

Total Head:

10.000 feet and 15.000 feet and 20.000 feet and 25.000 feet

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Height:

30.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.0

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

0.33 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

For use w/ flammable and combustible liquids, can handle various acids and corrosives; stainless steel float; min sump diameter 16.000 in.

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400