

View Online at <https://aerobasegroup.com/nsn/4320-01-174-4774>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Hydrocarbon fuels and oils

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Environmental Protection:**

Explosion proof

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

45.0 gallons per minute and 35.0 gallons per minute and 22.0 gallons per minute and 5.33 gallons per minute

**Total Head:**

10.000 feet and 15.000 feet and 20.000 feet and 25.000 feet

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Height:**

30.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

3.0

**Discharge Connection Thread Size And Series/type Designator:**

1.250-11-1/2 npt

**Prime Mover Power Rating:**

0.33 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

For use w/ flammable and combustible liquids, can handle various acids and corrosives; stainless steel float; min sump diameter 16.000 in.

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400