

View Online at <https://aerobasegroup.com/nsn/4320-01-174-9055>

Mounting Type:

Flange

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Close coupled

Media For Which Designed:

Hydrocarbon fuels and oils

End Application:

Crane, truck mtd, koehring co, model s888

Maximum Discharge Flow Rate:

11.5 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Counterclockwise

Rotary Pump Design:

Vane

Operation Method:

Powered

Drive Shaft Type:

Machine keyway

Drive Shaft End Diameter:

0.750 inches

Drive Shaft Length:

2.504 inches

Unpackaged Unit Length:

9.000 inches

Unpackaged Unit Width:

5.100 inches

Unpackaged Unit Height:

4.000 inches

Discharge Connection Thread Size And Series/type Designator:

1.062-12 un

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 nptf

Special Features:

Discharge port opposite side from intake

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400