

View Online at <https://aerobasegroup.com/nsn/4320-01-174-9055>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**End Application:**

Crane, truck mtd, koehring co, model s888

**Maximum Discharge Flow Rate:**

11.5 gallons per minute

**Discharge Pressure:**

100.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1200.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Counterclockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Machine keyway

**Drive Shaft End Diameter:**

0.750 inches

**Drive Shaft Length:**

2.504 inches

**Unpackaged Unit Length:**

9.000 inches

**Unpackaged Unit Width:**

5.100 inches

**Unpackaged Unit Height:**

4.000 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 un

**Intake Connection Thread Size And Series/type Designator:**

1.250-11-1/2 nptf

**Special Features:**

Discharge port opposite side from intake

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400