## NSN 4320-01-177-5346

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-177-5346

Prime Mover Quantity:  1 Prime Mover Cooling Medium: Air Mounting Type: Base Stage Quantity:  1 Intake Connection Quantity:
Prime Mover Cooling Medium: Air Mounting Type: Base Stage Quantity:
Air  Mounting Type:  Base  Stage Quantity:
Mounting Type: Base Stage Quantity:
Base Stage Quantity: 1
Stage Quantity:
1
·
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Pump Quantity:
2
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
40.0 gallons per minute
Discharge Pressure:
20.0 pounds per square inch gage
Total Head:
3.000 feet
Operating Speed At Rated Capacity:
3520.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
2
Centrifugal Pump Impeller Suction Type:
Double
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

## **NSN 4320-01-177-5346**Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:
3.0
Discharge Connection Thread Size And Series/type Designator:
1.250-11-1/2 npt
Intake Connection Thread Size And Series/type Designator:
1.250-11-1/2 npt
Prime Mover Power Rating:
20.000 horsepower
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400